

# NO6320T

## Polymeric Three-layer single-penetration

### Description :

Film: 150 micron Macromolecular PVC polymeric film  
 Adhesive: Transparent Adhesive  
 Liner: 100gsm perforated paper+70gsm PEK paper  
 Width: 1.27/1.37/1.52m

### Features :

- 1、 One side visual, sun-shade and privacy protection; Hole size is 1.60mm, perforation is 40%.
- 2、 This product is recommended to use UV printing; Also suitable for various solvent ink and Eco-solvent ink.

### Application :

Apply for glass, also suitable for transparent acrylic plate、 PVC、 PET transparent plate and so on  
 This product is recommended to use UV spraying; also suitable for various solvent ink and Eco-solvent ink

### Technical data :

Testing condition: Indoor temperature 23±2°C; Relative humidity 50±5%; Use aluminum, glass, steel plate as the base material for testing.

Test Items	Units	Test method	Average value
Thickness PVC	Micron	GB/T6672-2001	150±10
Weight-Liner	g/m <sup>2</sup>	GB4669-1995	140±10
Weight -finished product	g/m <sup>2</sup>	GB4669-1995	280±20
24h, 180°peel	N/25mm	FTM 1	≥4
Dimensional stability MD	mm	FTM 14	≤1.5
Dimensional stability CD	mm	FTM 14	≤1.0
Tensile strength MD	N/25 mm	GB/T1040.1-2006	≥35
Tensile strength CD	N/25 mm	GB/T1040.1-2006	≥20
Construction Temperature	°C		20±10
Applicable Temperature	°C		-20 ~ +70

All technical data is subject to change without prior notice

### Storage condition :

All NAR products always need to be stored in the original packing and with the original protection materials, preferably stored hermetically, no more than 6 layers if stored horizontally. Do not expose in direct sunlight or heat sources. Shelf life will be two year with temperature of 25°C±5°C and relative humidity of 50±15%.

### Production and Application Environment :

Production environment: temperature of 25±5°C, relative humidity of 50%±10%, clean dust-free environment without suspended matter; please move the materials to the printing environment 24 hours before printing. Test prior to use and remain enough edge margins when printing.

Application environment: temperature of 20±10°C, relative humidity of 50±10%; Pasting on flat, smooth and clean surface

without floating dust and shedding; It is necessary to take more than 2 hours for maintenance before laminating.

### Warranty Condition :

- 1、Warranty date is two years: One way vision product need accord with storage condition, preferably use with 6 months.
- 2、Prosecution date: from the product manufacture date, no-acceptance for overdue product.

### Important remark :

The information mentioned in this product data sheet is based upon tests that were executed by NAR, and that we consider to be reliable. Environment humidity more than 70% in different district will decrease the printing result.

### Application :



**NAR**  
IDEAS FOR SIGN