



# CPX80I

## 5G Industrial Outdoor CPE

CAT20

5G NR/LTE/WCDMA

RS485/RS232

IP67

The CPX80I from BTI WIRELESS is a 5G Industrial Outdoor CPE. It supports various 4G/5G spectrums and ultra-high speed in a ruggedized form factor. This product offers industrial-grade environmental qualifications while providing high speed data services for the bandwidth-intensive applications. Up to IP67 with water-proof, shock-resistant, and lightning-proof, combined to ensure the quality of wireless communication under different outdoor environments.

## KEY FEATURES

- Qualcomm SDX55 chipset solution
- 5G NR and LTE-A CAT20 dual mode
- Supports BOTH SA and NSA
- Global/CBRS bands supported
- Ruggedized and anti-vibration design
- Powerful software features, supporting all router features
- Supports Wi-Fi 6
- Web, TR069 and SNMP based device management
- Supports 2.5G WAN/LAN & 1G LAN and diverse industry interfaces
- IP67 rating for outdoor environment

## APPEARANCE



## HARDWARE SPECIFICATIONS

<b>Module</b>	Quectel RM500Q-GL	
<b>Cellular Bands</b>	5G NR	n1/n2/n3/n5/n7/n8/n12/n20/n25/n28/n38/n40/n41/n48/n66/n71/n77/n78/n79
	LTE	<u>LTE-FDD</u> : B1/B2/B3/B4/B5/B7/B8/B12/B13/B14/B17/B18/B19/B20/B25/B26/B28/B29/B30/B32/B66/B71 <u>LTE-TDD</u> : B34/B38/B39/B40/B41/B42/B43/B46/B48
	WCDMA	B1/B2/B3/B4/B5/B8/B19
<b>GNSS</b>	GPS/GLONASS/BeiDou/Galileo	
<b>WLAN</b>	MIMO 2*2 Wi-Fi 6	
<b>Network Mode</b>	Supports SA/NSA	
<b>External Port</b>	1 x M12 for power supply 1 x M12 for 10/100/1000Mbps compatible GE port 1 x M12 for 2.5GHz GE port 1 x M12 for RS232 + 2 x DI + 2 x DO	

	1 x M12 for RS485 2 x Nano SIM Slot (4FF, Dual SIM Single Active)
<b>Antenna Port</b>	3 x TNC connector for NR&LTE antenna 1 x TNC connector for NR&LTE&GNSS antenna 2 x TNC connector for 2.4&5GHz Wi-Fi antenna
<b>LED Indicators</b>	1 x power indicator 1 x network status indicator 1 x RSSI indicator
<b>Button</b>	1 x reboot or restore button
<b>MIMO</b>	DL 4*4 MIMO UL 2*2 MIMO
<b>ENDC</b>	Supported
<b>Tx/Rx</b>	2Tx/4Rx (n41/n77/n78/n79) 1Tx/4Rx (other LTE/NR bands)
<b>Power Supply</b>	DC 12~36V
<b>Power Consumption</b>	< 24W
<b>Dimensions</b>	250 x 171 x 61mm   9.84 x 6.73 x 2.40 in
<b>Weight</b>	≈2KG   4.41 lbs
<b>Humidity</b>	Operation/Storage: 5% - 95% (non-condensing)
<b>Temperature</b>	Operating temperature: -40 °C ~ +70 °C   -40 °F ~ +158 °F Storage temperature: -40 °C ~ +85 °C   -40 °F ~ +185 °F

## SOFTWARE SPECIFICATIONS

<b>Data Services</b>	4 x APNs	
	Multiple PDN	
	IPV4/IPV6 compliance	
<b>LAN</b>	IEEE 802.1Q VLAN	
	DHCP V4/V6	
	DNS and DNS proxy	
	DMZ	
	UPNP	
	ALG	
	ARP/ICMP/IGMP	
	MAC address filtering	
<b>Management</b>	Version management: Image checksum	
	HTTP/FTP auto-upgrade	
	TR069	Upload/ Download the ACS specified file
		Download the configuration file

		Configure & queries parameters	
		Remote upgrade	
		Remote debugging operations	
		Cycle monitor	
	SNMP		
	WebGUI/ CLI		Various level of user login priority with different limitation and display
			Encryption backup current settings and restore the backup settings
			Export current diagnosis results and operation logs
	Diagnostics		Statistics of LAN link status, transmit and receive traffic and up time
	USIM PIN management and card authentication		
	USIM activation		
	NAT/Bridge mode		
	Port mirror/Port forwarding		
	VPN & Routing	Static Routing	
IPSec			
PPTP			
GRE tunnel			
L2TP V2/V3			
Security	Firewall		
	Mac address filtering		
	IP address filtering		
	URL filtering		
	Access control		
	HTTPS login from WAN		
	DDOS attack protection		
	Hierarchical user management		

## COMPLIANCE SPECIFICATIONS

Environment Compliance	Protection rating: EN60529:IP67
	Salt mist: IEC68-2-11,72H
	Shock: IEC60068-2-27/EN50155/EN61373
	Free Fall: IEC60068-2-32 (1 meter height with package)
	Vibration: IEC60068-2-6/EN50155/EN61373

Contact Us

[www.btiwireless.com](http://www.btiwireless.com)

[sales@btiwireless.com](mailto:sales@btiwireless.com)