

FEMTOCELL sCELL-EF DATASHEET



sCELL-EF

LTE Enterprise Femtocell

2 x 2 MIMO

2 x 125mw

64 Concurrent Users

128 RRC Connected Users

The sCELL-EF from SUNWAVE is an enterprise-level 4G integrated Femto applying LTE technology. The product connects to the backbone network through wired backhaul and provides LTE access for terminals. It supports the transmission of voice and data with indoor wireless broadband coverage.

FEMTOCELL sCELL-EF DATASHEET

KEY FEATURES

- Integrated design of baseband and radio head
- Based on 3GPP LTE technology with high-speed data services
- Supports 5 MHz, 10 MHz, 15 MHz, 20 MHz bandwidth
- Convenient networking, plug and play solution, easy and flexible deployment
- External high-gain antenna for various usage scenarios
- Built-in DHCP server, DNS client and NAT functions, powerful high-speed routing capabilities
- Plentiful security service provides real-time protection, to prevent potential security risks and illegal intrusion
- Web-based management, convenient and intuitive
- Complete network management function
- Humanized indicator light, easy to observe and manage equipment status
- IP20 protection level

APPEARANCE



INTERFACE SPECIFICATIONS

INTERFACE NAME	QUANTITY	INTERFACE TYPE	INTERFACE DEFINITION
WAN/ PoE	1	RJ45	Data return and PoE+ power supply interface
LAN	1	RJ45	Local debugging interface
USIM	1		USIM card slot
SFP (Optional)	1	SFP	Data transmit back to optical interface
DC 12V	1	DC Socket	12V DC power supply interface
RST	1		Manual reset device button
GPS	1	SMA	GPS antenna interface

HARDWARE SPECIFICATIONS

Work Style	LTE FDD
-------------------	---------

FEMTOCELL sCELL-EF DATASHEET

Working Frequency	B1/3
Working Bandwidth	5 MHz/ 10 MHz/ 15 MHz/ 20 MHz
Transmit Power	2 x 21 dBm
Synchronization	Supports GPS, IEEE 1588 V2, IEEE 1588 ACR and air interface synchronization
Backhaul Method	RJ-45 ethernet port (1GE), SFP optical port
MIMO	2 x 2
Equipment Size	220 x 220 x 39 mm 8.66 x 8.66 x 1.54 in
Installation Method	Wall hanging, ceiling, desktop
Power Consumption	< 15W
Power Supply	220V AC to 12V DC power adapter, PoE+
Weight	< 0.65 kg 1.43 lbs
Equipment Capacity	< 1.9 L

SOFTWARE SPECIFICATIONS

Technical Standard	3GPP Release 12
Peak Rate (20 MHz Bandwidth)	DL: 150 Mbps (64QAM)/ UL: 75 Mbps (64QAM)
Operational Capacity	Supports 64 concurrent users, 128 RRC connected users
Scheduling Method	3GPP standard QCI
Modulation	Downlink: QPSK, 16QAM, 64QAM Uplink: QPSK, 16QAM, 64QAM
Voice Solution	VoLTE
SON	Supports automatic configuration, ANR and PCI conflict detection
Network Management Interface	Supports TR069 interface protocol
MTBF	< 150,000 hours
MTTR	< 1 hour
O&M	<ul style="list-style-type: none"> Remote/local maintenance, based on SSH protocol Online status management Performance statistics Fault management Configuration management Local or remote software upgrade and loading Supports log Connectivity diagnosis Self-start and self-configuration deployment Alarm reporting Supports KPI reporting User information tracking

FEMTOCELL sCELL-EF DATASHEET

ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-5 °C ~ +45 °C +23 °F ~ +113 °F
Humidity	10% ~ 95%

Contact Us Today

en.sunwave.com